

CASING SIZES
Threaded and Couple Type

O.D.		I.D.	Wt. Per Ft.		Thd/ Inch		Taper/Ft.		Length of Male Thread				Round "V" Form				Coupling Dia.	
In.	MM	In.	Plain	Thd. & Cplg.	R n d	V	Rnd	V	Short	Long	Short	Long	Short	Long	Short	Long	Rnd	"V"
4-1/2	114,3	4.090		9.50	8		3/4		2.000	--	1.407	--	6-1/4	--	3-5/8	--	5.000	
		4.052	9.40	10.23	8	14	3/4		2.625	--	--	--	6-1/4	--	--	--	5.000	5.021
		4.000		11.35	8		3/4	3/8	2.625	3.000	--	--	6-1/4	--	--	--	5.000	
		3.920		13.04	8		3/4		--	3.000	--	--	6-1/4	7	--	--	5.000	--
5	127,0	4.560	11.23	11.50			3/4	-	2.500	--	--	--	6-1/2	--	--	--	5.563	--
		4.494	12.83	13.00		- 10	3/4	3/8	2.750	3.375	2.550	--	6-1/2	7-3/4	6-5/8	--	5.563	5.491
		4.408	14.87	15.00	88	10	3/4	3/8	2.750	3.375	2.550	3.300	6-1/2	7-3/4	6-5/8	8	5.563	5.750
		4.276	17.93	18.00	88	10	3/4	3/8	--	3.375	2.550	3.300	6-1/2	7-3/4	6-5/8	8	5.563	5.750
5-1/2	139,7	5.012	13.70	14.00			3/4		--	2.750	3.300	6-3/4	--		8	6.050	6.155	
		4.950	15.35	15.50			3/4	3/8	2.875	3.500	--	--	6-3/4	8	7-1/8	--	6.050	-
		4.892	16.87	17.00	88	10	3/4	3/8	2.875	3.500	2.750	3.300	6-3/4	8	- 7	8	6.050	6.155
		4.778	19.81	20.00	88	10	3/4	3/8	2.875	3.500	2.750	3.300	--	8	1/8 7-	8	6.050	6.155
		4.670	22.54	23.00	8	10	3/4	-	--	3.500	--	--	8	1/8 --	--	6.050	-	
6-5/8	168,3	6.049	19.49	20.00			3/4			3.875	3.000	3.800		8-3/4 8-	7-5/8	9	7.390	7.390
		5.291	23.58	24.00			3/4	3/8	3.125	3.875	3.000	3.800	7-1/4	3/4 8-	7-5/8	9	7.390	7.390
		5.791	27.65	28.00	88	10	3/4	3/8	3.125	3.875	3.000	3.800	7-1/4	3/4 8-	7-5/8	9	7.390	7.390
		5.675	31.20	32.00	88	10	3/4	3/8	--	3.875	--	--	--	3/4	-	--	7.390	-
7	177,8	6.538	16.70	17.00			3/4		--	--	--						7.656	
		6.456	19.54	20.00			3/4		--	3.000	--	--		9			7.656	--
		6.366	22.63	23.00		-	3/4	-	2.375	4.000	3.000	4.050	7-1/4	9	--		7.656	7.750
		6.276	25.66	26.00		10	3/4	3/8	3.125	4.000	3.000	4.050	7-1/4	9	7-5/8	--	7.656	7.750
		6.184	28.72	29.00	88	10	3/4	3/8	3.125	4.000	--	--	7-1/4	9	7-5/8	9-1/2	7.656	7.750
		6.094	31.68	32.00	88	10	3/4	3/8	3.125	4.000	--	--	7-1/4	9	7-5/8	9-1/2	7.656	-
		6.004	34.58	35.00	88		3/4		--	4.000	--	--	--	9	--	--	7.656	--
		5.920	37.26	38.00	88		3/4		--	4.000	--	--	--	9	--	--	7.656	-

Casing Sizes
Threaded and Coupled Type
2

O.D.		I.D.	Wt. Per Ft.		Thd/Inch		Taper/Ft.		Length of Male Thread				Coupling Length				Coupling Dia.		
In.	MM	In.	Plain	Thd. & Cplg.	Rnd	V	Rnd	V	Short	Long	Short	Long	Short	Long	Short	Long	Rnd	"V"	
7-5/8	193,7	7.025	23.47	24.00	8	-	-	-	3.250	-	3.250	-	7-1/2	-	9	-	8.500	-	
		6.696	25.56	26.40	8	-	-	-	3.250	4.125	3.250	-	7-1/2	1/4 9-	7-1/2	-	9	8.500	-
		6.875	29.04	29.70	8	8	3/4 3/4	3/4	-	4.125	-	4.125	-	1/4 9-	7-1/2	1/4 9-	8.500	8.500	
		6.765	33.04	33.70	8	8	3/4 3/4	3/4	-	4.125	-	4.125	-	1/4 9-	7-1/2	1/4 9-	8.500	8.500	
		6.625	38.05	39.00	8	8	3/4 3/4	3/4	-	4.125	-	4.125	-	1/4	-	1/4	-	8.500	8.500
8-5/8	219,1	8.097	23.57	24.00	-	-	-	-	-	-	-	-	-	-	-	-	9.625	-	
		8.017	27.02	28.00	-	-	-	-	-	-	-	-	-	-	-	-	9.625	-	
		7.291	31.10	32.00	88	-	-	-	3.000	4.500	-	-	7-3/4	-	-	8	-	9.625	-
		7.825	35.14	36.00	88	8	3/4 3/4	3/4	3.375	4.500	3.000	-	7-3/4	10	1/8 8-	10-3/4	9.625	9.625	
		7.725	39.29	40.00	8	8	3/4 3/4	3/4	3.375	4.500	3.375	4.75	7-3/4	10	1/8 8-	10-3/4	9.625	9.625	
		7.625	43.39	44.00	8	8	3/4 3/4	3/4	3.375	4.500	3.375	4.75	7-3/4	10	1/8	-	10	9.625	9.625
7.511	48.00	49.00	8	8	3/4 3/4	3/4	-	4.500	-	4.75	-	10	-	3/4	-	9.625	9.625		
9-5/8	244,5	9.001	31.03	32.30	-	-	-	-	-	-	-	-	-	-	-	11	10.625	-	
		8.921	34.86	36.00	8	-	3/4	-	4.750	-	5.250	-	10-1/2	-	8	3/4 11-	10.625	10.625	
		8.835	38.94	40.00	88	8	3/4	3/4	3.375	4.750	3.250	5.250	7-3/4	10-1/2	1/8 8-	3/4 11-	10.625	10.625	
		8.755	42.70	43.50	88	8	3/4 3/4	3/4	3.375	4.750	3.250	5.250	7-3/4	10-1/2	1/8 8-	3/4 11-	10.625	10.625	
		8.681	46.14	47.00	8	8	3/4 3/4	3/4	3.375	4.750	3.250	5.250	7-3/4	10-1/2	1/8	-	3/4 11-	10.625	10.625
8.535	52.85	53.50	8	8	3/4 3/4	3/4	-	4.750	-	5.250	-	10-1/2	-	3/4	-	10.625	10.625		
10-3/4	273,0	10.192	31.20	32.75	-	-	-	-	2.750	-	-	-	-	-	-	-	11.750	-	
		10.050	38.88	40.50	8	-	3/4	-	3.500	-	3.625	5.375	-	-	8-1/8	-	12	11.750	11.750
		9.950	44.22	45.50	88	8	3/4 3/4	3/4	3.500	-	3.625	5.375	8	-	8-1/8	12	11.750	11.750	
		9.850	49.50	51.00	88	8	3/4 3/4	3/4	3.500	-	3.625	5.375	8	8	-	8-1/8	12	11.750	11.750
		9.760	54.21	55.50	8	8	3/4 3/4	3/4	3.500	-	3.625	5.375	8	8	-	8-1/8	12	11.750	11.750